

C07c HIGH DENSITY BOX HEADER STRAIGHT (1.27mm * 2.54mm) PITCH:1.27mm

SPECIFICATIONS

Material

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze

Electrical

Current Rating : 1 Amp





Contact Resistance : 30 mΩ max.

Insulation Resistance : 1000 MΩ min.


Dielectric Withstanding Voltage : 250V AC for 1minute

Operating Temperature : -40°C to +105°C


◆ Mating Suggestion : A07a series.



POSITION	A	B	C
10	13.95	11.75	5.08
20	20.30	18.10	11.43
26	24.11	21.91	15.24
30	26.65	24.45	17.78
34	29.19	26.99	20.32
40	33.00	30.80	24.13
50	39.35	37.15	30.48
60	45.70	43.50	36.83
68	50.78	48.58	41.91
70	52.05	49.85	43.18
80	58.40	56.20	49.53
90	64.75	62.55	55.88
100	71.10	68.90	62.23



P.C. BOARD LAYOUT FOR
20, 40, 60, 68, 80, 100



P.C. BOARD LAYOUT FOR
10, 26, 30, 34, 50, 70, 90

HOW TO ORDER:

C07c - - - -

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.INSULATOR COLOR
10 20 26 30 34 40 50 60 68 70 80 90 100	B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	1. BLACK