


Tabbed Lithium Batteries

Tabbed 3V Lithium Batteries for P.C. Board Mounting – Two Pins Horizontal



RENATA No.	Nominal capacity (mAh)	Weight (g)	Maximum dimensions (mm)				
			A	B	C	D	E
CR1216FH	25	0.9	12.5	12.7	11.00	2.4	6.3
CR1220FH	38	1.0	12.5	12.7	11.00	2.8	6.7
CR1225FH	48	1.1	12.5	12.7	11.00	3.3	7.2
CR1616FH	50	1.3	16.0	16.2	12.70	2.4	6.3
CR1620FH	68	1.4	16.0	16.2	12.70	2.8	6.7
CR1632FH	125	2.0	16.0	16.2	11.00	3.9	7.8
CR1632FH1	125	2.0	16.0	16.2	15.20	3.9	7.8
CR2016FH	80	1.9	20.0	20.2	15.20	2.4	6.3
CR2016FH1	80	1.9	20.0	20.2	20.40	2.4	6.3
CR2025FH	170	2.5	20.0	20.2	15.20	3.3	7.2
CR2025FH1	170	2.5	20.0	20.2	20.40	3.3	7.2
CR2032FH	235	3.0	20.0	20.2	15.20	3.9	7.8
CR2032FH0	235	3.0	20.0	20.2	10.35	3.9	7.8
CR2032FH1	235	3.0	20.0	20.2	20.40	3.9	7.8
CR2032FH2	235	3.0	20.0	20.2	22.50	3.9	7.8
CR2325FH	190	3.2	23.0	23.2	20.40	3.3	7.2
CR2430FH	285	4.3	24.5	24.7	20.40	3.9	7.8
CR2430FH1	285	4.3	24.5	24.7	15.20	3.9	7.8
CR2450NFH	540	6.1	24.5	24.7	20.40	5.8	9.7
CR2477NFH	950	8.4	24.5	24.7	20.40	8.5	12.4