



JQG BATTERIES - Der zuverlässige Partner seit 1954



Ready to use:
Unsere starken Lithium
Ionen Standard-Packs
STP 4-770 mAh, STP 5-1100 mAh
und STPL 10-1850 mAh.

STP 4

Battery Dimensions [mm]

Length (L)	Max 52.60
Width (W)	Max 35.35
Thickness (T)	Max 4.45 (delivery status) Max 5.00 (after cycling, center)
Contacts	+ / NTC / -

Electrical Parameter

Nominal Voltage [V]	3.7 (average)
Typical capacity [mAh]	770 (0.2C/3.0V at 20°C)
Minimum capacity C [mAh]	750 (0.2C/3.0V at 20°C)
Max. Charge [mA]	750
Max. Charge Voltage [V]	4.20
Max. cont. Discharge [mA]	1500

STP 5

Battery Dimensions [mm]

Length (L)	Max 53.45
Width (W)	Max 34.25
Thickness (T)	Max 5.70 (delivery status) Max 6.50 (after cycling, center)
Contacts	+ / NTC / - NTC 10kOhm+1% B-3435 +1%

Electrical Parameter

Nominal Voltage [V]	3.7 (average)
Typical capacity [mAh]	1100 (0.2C/3.0V at 20°C)
Minimum capacity C [mAh]	1000 (0.2C/3.0V at 20°C)
Max. Charge [mA]	1000
Max. Charge Voltage [V]	4.20
Max. cont. Discharge [mA]	2000

STPL10

Battery Dimensions [mm]

Length (L)	Max 52.45
Width (W)	Max 34.10
Thickness (T)	Max 11.50 (delivery status) Max 12.50 (after cycling, center)
Contacts	+ / NTC / - NTC 100kOhm+5%

Electrical Parameter

Nominal Voltage [V]	3.7 (average)
Typical capacity [mAh]	1850 (0.2C/3.0V at 20°C)
Minimum capacity C [mAh]	1800 (0.2C/3.0V at 20°C)
Max. Charge [mA]	1800
Max. Charge Voltage [V]	4.20
Max. cont. Discharge [mA]	1800

Wir bieten Ihnen auch Standard-Batteriekontakte auf Anfrage.



UEBK-12549 UEBK-12551

Alle Zellen optional mit 3 pol. Kabel
und Stecker lieferbar.

Gerne können Sie Muster bei uns bestellen:

WH Hofstädtler I.E. GmbH
Telefon: 02622 / 21550-0
Telefax: 02622 / 21550-5
A-2700 Wiener Neustadt Zemendorfer Gasse 7
office@hofstaedtler.com www.hofstaedtler.com

